

RISK FACTORS

- **Sharp objects** – can cause bursting of the cover;
- **Humidity** – continuous excessive humidity at using or storage can cause the corrosion of metal parts or penetration of mustiness;
- **Negative action of substances** – acid, lye, oil, petrol, toluene, acetone, kerosene and similar solvents can cause deterioration of the cover.

STORAGE

At long-term storage and also short-term storage, store the cover in clean condition at the room temperature (15 up to 35)°C minimum 1.5 m from radiant heat source, in a dark, dry and clean place clear of harmful substances (acids, lye, oil, petrol, toluene, acetone, kerosene and similar solvents), solar radiation and rodents so that the damage danger will be minimized.

DISPOSAL WAY OF COVER AND PACKING

Dispose **the cover** in a standard way like any municipal waste with storage on municipal waste landfill places.

Recycle or store the **packing** with municipal waste.

Another disposal is non-permissible!

CONDITIONS OF GUARANTEE AND LIFETIME

The guarantee period of the cover for the BEDI child car seat is 24 months from the date of sale. The manufacturer provides the free of charge repair or compensation for defects of material or production character.

When observing the recommended maintenance and service instructions, the minimal lifetime of the cover is 5 years.

THE GUARANTEE AND AFTER GUARANTEE REPAIR

The guarantee and after guarantee service is provided by the manufacturer:

GUMOTEX, a. s.
Mládežnická 3A, č. p. 3062
690 75 Břeclav
Czech Republic

GUMOTEX

GUMOTEX, akciová společnost
Mládežnická 3A, č. p. 3062
690 75 Břeclav

Instructions for use


COVER FOR THE CHILD CAR SEAT **BEDI**




The cover for the child car seat BEDI is intended to improve the sitting comfort of the child in the BEDI car seat and as protection against spotting of the child car seat.

COVER PUTTING ON THE BEDI CHILD CAR SEAT


- Take the cover out of the packing and spread it out;
- Spread out the deflated BEDI child car seat, inflate slightly, then fold it lengthwise and insert through one of the side openings into the cover so that the "ears" (belt holders) of the child car seat pass the openings in the upper part of the cover;
- Put straight the lower and upper parts of the child car seat (seat and backrest) in the cover;
- Inflate the BEDI child car seat according to the User's guide – check during the inflation, whether the cover is put on well and adjust possible inequalities before the complete inflation;
- Inflate the child car seat after a while;
- Fix the cover on the sides and tie the laces.



Unpack the seat and the cover.




Inflate the seat slightly.




Take the car seat "ears" (belt holders) out of the cover.



Put on the cover on the whole seat and inflate.



Tie the cover laces and pull the cover over the valve.



Seat in cover.

TAKING OFF THE COVER

- Untie the laces on the sides;
- Deflate the BEDI child car seat according to the User's guide for the BEDI child car seat;
- Insert the "ears" (belt holders) of the car seat into the cover carefully;
- Fold the car seat inside of the cover lengthwise;
- Put the car seat out of the cover;
- Fold the cover in halves and attach into the casing with the folded BEDI child car seat.

COVER MATERIAL 100 % polyester silk, cotton edging

COVER PACKING polyethylene bag (PE)

HEALTH HARMLESSNESS

The cover is harmless for the health even for children younger than 3 years old and meets the requirements stipulated in Oeko-Tex Standard 100.

COVER MAINTENANCE

